

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name **PROMASEAL ACRYLIC SEALANT**
Synonyms FYRE SEAL MASTIC, PROMAT PROMASEAL ACRYLIC SEALANT.
Uses SEALANT, FIRE RETARDANT, FIRE RATED JOINT SEALANT.
Supplier Name PROMAT AUSTRALIA PTY LTD
Address 1 Scotland Road, MILE END SA, 5031, AUSTRALIA
Telephone (08) 8352 6759
Fax +61 8 8352 1014

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO NOHSC CRITERIA
NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	Conc.	CAS No.
MINERAL FILLERS		30 - 60%	Not Available
ACRYLIC POLYMER		10 - 30%	Not Available
PLASTICISER		1 - 10%	Not Available
ADDITIVES		1 - 10%	Not Available
WATER	H2O	Not Available	7732-18-5

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing for at least 15 minutes.

Inhalation If exposure occurs leave exposure area immediately. If irritation persists, seek medical attention.

Skin Gently flush affected areas with water. Seek medical attention if irritation develops.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor. If swallowed, do not induce vomiting.

Advice To Doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flammability Non flammable - combustible when dry. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

Fire and Explosion Non flammable. Evacuate area and contact emergency services. Toxic gases (hydrocarbons, carbon oxides) may be evolved when heated. Remain upwind and notify those downwind of hazard. Wear full protective equipment (see spill above) including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Extinguishing Non flammable. Prevent contamination of drains or waterways, absorb runoff with sand or similar.

Hazchem Code None Allocated

**Colour
Rating
GREEN**

6. ACCIDENTAL RELEASE MEASURES

Spillage If spilt (bulk), collect and reuse where possible. Wear splash-proof goggles, PVC/rubber gloves, coveralls or protective clothing and boots. Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. Prevent spill entering drains or waterways. Absorb with sand or similar and place in sealable containers for disposal.

7. HANDLING AND STORAGE

Handling Use safe work practices to avoid eye or skin contact and inhalation. Observe good personal hygiene. Prohibit eating, drinking and smoking in contaminated areas. Wash hands before eating. Remove contaminated clothing and protective equipment before entering eating areas.

Storage Store in cool, dry, well ventilated area, removed from oxidising agents, acids and foodstuffs. Ensure product is adequately labelled, protected from physical damage and sealed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation Use with adequate natural ventilation. Open windows and doors where possible. In poorly ventilated areas, mechanical extraction ventilation is recommended.

Exposure Standards An exposure standard (TWA, STEL, WES) has not been allocated to the ingredients contained in this product.

PPE Wear splash-proof goggles and PVC or rubber gloves. When using large quantities or where heavy contamination is likely, wear coveralls. Where an inhalation risk exists, wear a Type A (Organic vapour) Respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: GREY/WHITE PASTE
Odour: ACRYLIC ODOUR
pH: NOT AVAILABLE
Vapour Pressure: NOT AVAILABLE
Vapour Density: NOT AVAILABLE
Boiling Point: NOT AVAILABLE
Melting Point: NOT AVAILABLE
Evaporation Rate: NOT AVAILABLE
Solubility (water): SOLUBLE
Specific Gravity: 1.6
% Volatiles: NOT AVAILABLE
Flammability: NON FLAMMABLE
Flash Point: NOT RELEVANT
Upper Explosion Limit: NOT RELEVANT
Lower Explosion Limit: NOT RELEVANT
Autoignition Temperature: NOT AVAILABLE

10. STABILITY AND REACTIVITY

Reactivity Incompatible with oxidising agents (eg. hypochlorites, peroxides), acids (eg. nitric acid), and heat sources.

Decomposition Products May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

Colour
Rating
GREEN

11. TOXICOLOGICAL INFORMATION

- Health Hazard Summary** Low toxicity. This product may only present a hazard with direct eye contact or prolonged and repeated skin contact. This product may contain trace amounts of unreacted monomers, however due to product form and the low vapour pressure of this product, an inhalation hazard is not anticipated unless used in poorly ventilated areas.
- Eye** Low irritant. Exposure may result in irritation and lacrimation.
- Inhalation** Low irritant. Over exposure at high levels may result in mucous membrane irritation of the nose and throat with coughing. Due to the low vapour pressure of this product an inhalation hazard is not anticipated.
- Skin** Low irritant. Prolonged and repeated contact with the skin may result in mild irritation.
- Ingestion** Low toxicity. With large doses ingestion may result in nausea, vomiting and gastrointestinal irritation.

12. ECOLOGICAL INFORMATION

- Environment** This product is not anticipated to cause adverse effects to animal or plant life if released to the environment in small quantities. Not expected to bioaccumulate.

13. DISPOSAL CONSIDERATIONS

- Waste Disposal** For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. For larger amounts, contact the manufacturer for additional information. Prevent contamination of drains or waterways as aquatic life may be threatened and environmental damage may result.
- Legislation** Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

- Transport** Not classified as a Dangerous Good according to the Australian Code for the transport of Dangerous Goods by Road and Rail.
- UN Number** None Allocated
- DG Class** None Allocated
- Subsidiary Risk(s)** None Allocated
- Packing Group** None Allocated
- Hazchem Code** None Allocated

15. REGULATORY INFORMATION

- Poison Schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

16. OTHER INFORMATION

- Additional Information** The manufacturer reports that the ingredients in this product are on the Australian Inventory of Chemical Substances (AICS).

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

Colour
Rating
GREEN

16. OTHER INFORMATION cont.

ACRYLIC - WATER BASED COMPOUNDS: It should be noted that most water based paints and acrylic or thermoplastic resins may contain small percentage of solvents, usually less than 5%. The solvent is used as a dispersion agent for the resin of choice. This solvent component may present potential respiratory hazards only in poorly ventilated areas or when sprayed. Those individuals with existing skin disorders should avoid direct contact.

COLOUR RATING SYSTEM: Chem Alert reports are assigned a colour rating of Green, Amber or Red for the purpose of providing users with a quick and easy means of determining the hazardous nature of a product. Safe handling recommendations are provided in all Chem Alert reports so as to clearly identify how users can control the hazards and thereby reduce the risk (or likelihood) of adverse effects. As a general guideline a Green colour rating indicates a low hazard, an Amber colour rating indicates a moderate hazard and a Red colour rating indicates a high hazard.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made. Information provided by Risk Management Technologies is summarised for ease of use. Additional technical information is available by calling +61 8 9322 1711.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

ABBREVIATIONS:

mg/m³ - Milligrams per cubic metre

ppm - Parts Per Million

TWA/ES - Time Weighted Average or Exposure Standard.

pH - relates to hydrogen ion concentration - this value will relate to a scale of 0 - 14, where 0 is highly acidic and 14 is highly alkaline.

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

M - moles per litre, a unit of concentration.

IARC - International Agency for Research on Cancer.

MSDS Reviewed 1st January 2004

Date Printed 2nd September 2004

Report Status Chem Alert reports are compiled as an independent source of information by RMT's scientific department, based on the latest chemical and toxicological research and, where appropriate, in compliance with relevant standards, guidance notes and legislation. Where available the manufacturer's original MSDS is also provided to Chem Alert subscribers as a scanned image for their convenience. In many instances Chem Alert reports are compiled on behalf of manufacturers in which case they serve as the "Manufacturer's MSDS" and are clearly identified as such on the relevant reports.

Prepared By Risk Management Technologies
5 Ventnor Avenue, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Web: www.rmt.com.au

**Colour
Rating
GREEN**